Scalable AI: Bridging Theory, Understanding, and Practice

Fall 2026

UC Berkeley

Lecture 13. Introduction to Post-Training

Structured data, chat templates, tool use, preference tuning, RL with verifiable rewards, and evaluation

Fall 2026

Post-training turns a base model into an assistant



Each stage uses a different kind of data and adds different behaviors.

Roadmap for today

1. Post-training as structured data	How messages and tools become tokens, which tokens get gradient, and how the server reads them back
2. Tool use and structured outputs	Schemas, constrained decoding, untrusted tool results, and traces
3. The lifecycle	What each stage trains on, and why SFT comes before RL
4. SFT and preference tuning	Demonstrations, comparisons, reward models, DPO
5. RL with verifiable rewards	Checkers as rewards, GRPO, DeepSeek-R1-Zero, and environments
6. Evaluation	The many things a model is tested on, and why scores are hard to compare

1. Post-Training as Structured Data

Everything the model sees is a token sequence

Pre-training data is a stream of text, and post-training data has fields

Pre-training example

. . . the return window for most items is 30 days from delivery. To start a return, sign in and open Your Orders. Can I return a gift? Yes, gifts can be returned for store credit . . .

One long sequence. The model predicts every token.

Post-training example

system	You are a support agent for an online store.
user	Refund order A-1930.
assistant	`order_lookup("A-1930")`
tool	`{"status": "delivered"}`
assistant	It was delivered 3 days ago, so it can be refunded.
tools	`order_lookup`, `issue_refund`
label	a preferred and a rejected reply, or a check that the refund went through

Everything the model sees is a token sequence. Post-training data has turns, roles, and tools, and all of it has to be written into token sequences that the model can learn from.

Each capability is written into tokens in its own way

Multi-turn chat
roles and turns

`user: Hi` `assistant: Hello, how can I help?` `user: Refund A-1930.` `assistant: ...`

Tool use
schemas, calls, results

`# Tools` `Refund A-1930.` `<tool_call>{...}</tool_call>` `{"status": ...}` `It can be refunded.`

Reasoning
thinking, then the answer

`r's in strawberry?` `<think> s-t-r-a-w-b-e-r-r-y ...</think>` `There are 3.`

Structured output
a JSON schema

`schema: order_id, refund` `Refund A-1930.` `{"order_id": "A-1930", "refund": true}`

Preferences
chosen and rejected

`Can I return a gift?` `Yes, for store credit within 30 days.` ✓

`Can I return a gift?` `It depends on many policies.` ✗

Agent tasks
many steps, then an outcome

`task` `call` `result` `call` `result` `···` `call` `result` `checker: tests pass`

context | written by the model | thinking | tool or schema definitions

A chat template turns a structured record into one token sequence



The template ships with the tokenizer. The training loss mask, the serving parser, and evaluation prompts all rely on these tokens. Serving the same weights with a different template lowers output quality.

Tool definitions are pasted into the system prompt as text



The tool's name, description, and full JSON schema are pasted into the system prompt as text, ahead of the user's message. Each model family has its own layout, but in all of them the tools are prompt tokens.

OpenAI function calling guide. The rendered layout is illustrative.

The model writes the tool call, and the environment writes the result

user message

```
<|im_start|>user
Refund order A-1930.<|im_end|>
```

tool call — written by the model

```
<|im_start|>assistant
<tool_call>
{"name": "order_lookup",
 "arguments": {"order_id": "A-1930"}}
</tool_call><|im_end|>
```

tool result — written by the client

```
<|im_start|>tool
{"status": "delivered", "days_since_delivery": 3,
 "refundable": true}<|im_end|>
```

response — written by the model

```
<|im_start|>assistant
It was delivered 3 days ago, so it can be refunded.
Store credit or original payment?<|im_end|>
```

The client runs the call, appends the result, and the model continues the same sequence.

Reasoning models write their thinking between special tokens

user message	<|im_start|>user Refund order A-1930.<|im_end|>
thinking	<|im_start|>assistant <think>Refunds depend on the delivery date. Check it first.</think>
tool call	<tool_call>{"name": "order_lookup", ...}</tool_call>
tool result	<|im_start|>tool {"status": "delivered", "days_since_delivery": 3}
thinking	<think>3 days is inside the 30-day window.</think>
response	It can be refunded. Store credit or original payment?

The reasoning parser separates the thinking from the reply, and the product decides whether to show it. Qwen3's template drops thinking from earlier turns, while DeepSeek-V3.2 keeps it across tool calls until the next user message.

Qwen3 model card, best practices; DeepSeek-V3.2 (arXiv 2512.02556) §3.2.1.

Only the tokens the model should produce receive gradient



$$\mathcal{L}(\theta) = -\sum_{t=1}^{T} m_t \log p_\theta(x_t \mid x_{<t})$$

Trained on ($m_t = 1$)	**Context only** ($m_t = 0$)
assistant text, tool-call names and arguments, reasoning tokens	system prompt with tool schemas, user messages, tool results

The mask decides what the model learns to write and what it only learns to read. If tool results were left in the loss, the model would learn to invent tool outputs instead of waiting for them.

The server parses reasoning and tool calls back out of the tokens



The template writes structure into tokens during training, and the parser reads it back out during serving. vLLM and SGLang ship one parser per model family. If either side changes its tags, the other has to change with it.

Parsing the model's tool calls fails in a few predictable ways

Malformed JSON

```
{"order_id": "A-1930",}
```

parse error

Unknown tool

```
{"name": "refund_order", ...}
```

nothing to route to

Partial delimiter

```
<tool_ {"name": "order_lookup",
...
```

no call detected

Cut off by the length limit

```
{"name": "order_lookup", "argum
```

parse error

The server can retry, return the error to the model, or show it to the user, and each choice changes agent benchmark scores. Delimiters such as `<tool_call>` are registered as special tokens, so each is a single token that never appears in normal text.

Reformatting a tool schema changes the tokens the model was trained on



Both versions describe the same API. Version A is 37 tokens and B is 51, and almost every token is different.

A model trained on schemas written like A sees unfamiliar input when it is served B. Teams pick one fixed format for key order, spacing, and naming, and use it in both training and serving.

Token splits computed with tiktoken, o200k_base encoding.

Tool definitions take context space before the conversation starts



Number of tools in parentheses.

Every tool's name, description, and schema is sent with every request. These five servers take about 55,000 tokens, a quarter of a 200,000-token context window, before the user has said anything.

One fix is to send a search tool instead and load the full definitions only when the model asks for them. In Anthropic's tests this cut the tool tokens by 85% and also raised tool-selection accuracy.

Anthropic, Introducing advanced tool use on the Claude Developer Platform (Nov 2025).

Escaping code inside JSON arguments makes tool calls fail

JSON arguments

```
{"name": "write_file",
 "arguments": {
  "path": "hello.py",
  "content": "def greet():\n    print(\"hi\")"}}
```

The code has to be written as one JSON string, with every newline and quote escaped. One missed escape makes the call invalid.

XML-style arguments

```
<tool_call>write_file
<arg_key>path</arg_key>
<arg_value>hello.py</arg_value>
<arg_key>content</arg_key>
<arg_value>
def greet():
    print("hi")
</arg_value></tool_call>
```

The code is written as is. GLM-4.5 switched to this format for that reason, and DeepSeek-V4 reports fewer escaping errors with a similar one.

GLM-4.5 (arXiv 2508.06471) §3.1 Fig. 4; DeepSeek-V4 (arXiv 2606.19348) §5.1.1.

2. Tool Use and Structured Outputs

What the model does with tools, and what can go wrong

The tool protocol has four steps, and each one can be measured



Agent benchmarks such as BFCL and τ^2-bench score these steps separately, which tells you which kind of training data is missing.

The same four steps reappear as preference rubrics and as RL reward terms later in the lecture.

Constrained decoding enforces the schema but cannot make the values right



Illustration. Tokens that would break the schema are masked, and the rest are renormalized.

Structured-output APIs and grammar engines such as XGrammar mask every token that would make the output invalid. The output always parses.

If the model put little probability on the allowed tokens, the mask pushes it onto paths it rarely saw in training. The JSON is valid and the values inside it are often worse.

Forcing a strict format has also been measured to lower reasoning accuracy compared with answering freely.

Dong et al., XGrammar (arXiv 2411.15100); Tam et al., Let Me Speak Freely? (arXiv 2408.02442); OpenAI structured outputs guide.

Train on the schema you deploy

A schema the model never trained on

```
{"diagnosis": "seasonal allergies",
 "icd10_code": "J45.909",
 "confidence": 0.93,
 "differential": ["common cold"]}
```

The JSON is valid and the confidence looks precise. The code J45.909 is asthma, which does not match the diagnosis.

Stage	What to add
SFT	examples written in the exact deployed schema
Preference	pairs of valid JSON with right values against valid JSON with wrong values
RL	a reward that runs the schema validator and checks the values

Once the model assigns high probability to correct outputs in the schema, the decoding mask rarely has to intervene.

Tool results are untrusted input



Anything a tool returns, including web pages, emails, and files, can contain text written by an attacker. This is called indirect prompt injection.

Chat templates give tool results their own role so the model can tell them apart. Labs then train an instruction hierarchy, where lower-priority messages cannot override higher ones.

Servers add filters on untrusted sources and require confirmation before tools with side effects run.

Greshake et al., indirect prompt injection (arXiv 2302.12173); Wallace et al., The Instruction Hierarchy (arXiv 2404.13208).

A tool call is an action in a partially observed world



Each tool result is a small, compressed observation of a large system. From it the model has to infer what the user wants, which action moves toward it, and what is still unknown.

This is a planning problem under uncertainty. It is learned from multi-step traces and from RL in environments, because single-turn examples do not contain it.

A stored trace can be reused as SFT data or as RL data



A post-training example is a trace of inputs, actions, observations, and an outcome. Once stored, the same traces serve several objectives.

Traces sampled from the current model are on-policy, whether they are used for SFT or RL. Traces from a different model, or from people, are off-policy. Later slides show why this matters.

3. The Lifecycle

What each stage trains on, and why the stages come in this order

The same prompt sent to three models

Base model

pre-training only

```
How many times does the letter r
appear in strawberry?
How many times does the letter e
appear in elephant?
How many times does the letter s
appear in Mississippi?
How many vowels are in the word
banana?
...
```

Instruct model

SFT and preference tuning

```
How many times does the letter r
appear in strawberry?
The letter r appears 2 times in
strawberry.
```

Reasoning model

SFT, preference tuning, and RLVR

```
How many times does the letter r
appear in strawberry?
<think> Spell it out.  s t r a w b e
r r y.  The r's are at positions 3,
8, and 9.  That is three.  </think>
The letter r appears 3 times.
```

The base model treats the question as the start of a document and continues it. The other two have learned to answer in a turn, and the third has learned to check its work before answering.

Each stage trains on different data and fails in its own way



Bars are schematic. If one sample is right 1 time in 1,000, finding a single correct answer with 90% probability takes about 2,300 samples.

4. SFT and Preference Tuning

Demonstrations, comparisons, reward models, and DPO

SFT trains on demonstrations of the protocol

```
<|im_start|>system You are a support agent.<|im_end|>
<|im_start|>user Refund order A-1930.<|im_end|>
<|im_start|>assistant I'll look that up.
<tool_call>{"name": "order_lookup", "arguments":
 {"order_id": "A-1930"}}</tool_call><|im_end|>
<|im_start|>tool {"status": "delivered", "refundable": true}<|im_end|>
<|im_start|>assistant You are eligible. Store credit or
original payment?<|im_end|>
```

$$\mathcal{L}_{\mathrm{SFT}}(\theta) = -\sum_{t \in \text{assistant}} \log p_\theta(x_t \mid x_{<t})$$

A record holds the system instruction, the user turns, the assistant turns with their tool calls, the tool results, and often metadata such as a capability label or a quality score.

SFT teaches the template, the tool format, and a default style. Most of the capability gain from a small amount of SFT data comes from learning the format.

SFT only imitates. It has no way to say that one acceptable answer is better than another, and the model only ever sees good states, never its own mistakes.

A preference record is a comparison between two answers



Where the two answers come from	
on-policy	samples from the current model
off-policy	older checkpoints, other models, people

Who decides which is better	
people	experts for hard domains
a judge model	cheaper, with its own biases
a ranking	order K answers instead of two

Comparing two answers is easier than writing the best one, and it also shows what to avoid. Pairs help most when both answers come from the current model, so pipelines re-sample and re-label as training goes on.

Tajwar et al., Preference Fine-Tuning of LLMs Should Leverage Suboptimal, On-Policy Data (arXiv 2404.14367).

RLHF trains a reward model on comparisons, then optimizes against it



The reward model is trained with the Bradley–Terry loss

$$P(y^+ \succ y^- \mid x) = \sigma\big(r_\phi(x, y^+) - r_\phi(x, y^-)\big).$$

It turns comparisons, which people can make quickly, into a scalar score for any answer.

The RL objective is

$$\max_{\pi} \; \mathbb{E}\big[r_\phi(x, y)\big] - \beta \, \mathrm{KL}\big(\pi \,\|\, \pi_{\mathrm{ref}}\big).$$

The KL term keeps the policy near the SFT model, which protects capabilities and the tool format that the reward model does not score.

In InstructGPT, labelers preferred a 1.3B model trained this way over the 175B GPT-3 base model.

Ouyang et al., Training Language Models to Follow Instructions with Human Feedback (arXiv 2203.02155).

DPO optimizes the same objective without a reward model

The KL-regularized objective has a closed-form optimum

$$\pi^*(y \mid x) \propto \pi_{\text{ref}}(y \mid x)\, \exp\big(r(x,y)/\beta\big).$$

Solving for the reward gives

$$r(x,y) = \beta \log \frac{\pi^*(y \mid x)}{\pi_{\text{ref}}(y \mid x)} + \text{const.}$$

Substituting into Bradley–Terry gives a loss on preference pairs

$$-\log \sigma\left(\beta \log \tfrac{\pi_\theta(y^+)}{\pi_{\text{ref}}(y^+)} - \beta \log \tfrac{\pi_\theta(y^-)}{\pi_{\text{ref}}(y^-)}\right).$$

The gradient raises the chosen answer and lowers the rejected one. Pairs that the implied reward already ranks correctly get a small weight.

There is no reward model and no sampling loop. Each pair costs two forward passes through the policy and two through a frozen reference.

Well-tuned PPO still beats DPO in controlled comparisons, and the choice of preference data matters more than the choice of algorithm.

Rafailov et al., DPO (arXiv 2305.18290); Xu et al. (arXiv 2404.10719); Ivison et al. (arXiv 2406.09279).

Optimizing a learned reward too hard lowers the true reward



Curves follow the functional form $d(\alpha - \beta \log d)$ fit by Gao et al. with illustrative coefficients.

A reward model is a learned proxy. Past some distance from the starting policy, the policy finds answers the proxy likes and people do not.

The KL penalty from the RLHF objective limits that distance. Its weight β trades reward against drift.

This ceiling is one reason reasoning training moved to rewards that are checked rather than learned.

Gao, Schulman, Hilton, Scaling Laws for Reward Model Overoptimization (arXiv 2210.10760).

Preference labels have known biases

Bias	What happens	Common fix
Length	longer answers win even when they are not better, and optimizing for length alone recovers much of the RLHF gain	length-controlled rubrics and win rates
Confidence and style	an answer that sounds sure beats one that is correct	rubrics that check facts first
Agreement with the user	answers that agree with the user's stated view are preferred	pairs where the user is wrong
Inconsistent labelers	different people read the rubric differently	gold questions, agreement checks, calibration
Narrow prompts	pairs miss edge cases	adversarial and targeted prompts

For tool use, the rubric asks whether the model called a tool only when needed, chose the right one, gave valid arguments, and used the result. The same four checks appear in the tool protocol above.

Singhal et al., A Long Way to Go (arXiv 2310.03716); Sharma et al., Towards Understanding Sycophancy (arXiv 2310.13548).

Production preference tuning balances several objectives



Llama 2 trained separate helpfulness and safety reward models, because one model had trouble scoring both. During RL it used the safety score for prompts likely to be unsafe or when the safety score was low, and the helpfulness score otherwise.

Most reward models give one score for the whole answer. Per-token rewards give denser signal for long agent traces, but they are easier to exploit and need strong checks.

Touvron et al., Llama 2 (arXiv 2307.09288) §3.2.

Labels from a model can stand in for many human labels



First two groups are win rates against the SFT model.

An LLM labeler matched human labels within a point or two on helpfulness, at roughly a tenth of the cost.

Several open recipes use model-generated preferences. Zephyr trained on UltraFeedback labels, and Tülu 3 generates its preference data with models. Human labels are still used where models are unreliable.

After preference tuning, models follow instructions better, refuse more appropriately, and have better style and tool behavior. Correctness on hard problems is what the next stage targets.

Lee et al., RLAIF vs. RLHF (arXiv 2309.00267); Tunstall et al., Zephyr (arXiv 2310.16944); Tülu 3 (arXiv 2411.15124).

5. RL with Verifiable Rewards

Rewards that come from a checker instead of a learned model

RLVR uses a checker as the reward

Task	**Producing an answer**	**Checker $V(x, y)$**
Math with a final number	derive it	compare with the reference answer
Code and software fixes	write the program or patch	run the unit and integration tests
Structured output	fill in the schema	schema validator plus value checks
Formal proof (Lean)	write the proof	run the proof checker
Answers grounded in sources	search and combine	check that citations support the claims

$$\max_{\theta} \; \mathbb{E}_{x \sim \mathcal{D}} \; \mathbb{E}_{y \sim \pi_\theta(\cdot|x)} \big[V(x, y) \big]$$

The reward comes from code that checks the answer.
The name RLVR comes from Tülu 3.

Preference tuning asks which of two answers is better, and RLVR asks whether the task was done. A checker does not drift the way a learned reward model does, so it supports many samples per prompt and long runs.

Lambert et al., Tülu 3 (arXiv 2411.15124).

One RLVR step samples, checks, and updates



DeepSeek-R1-Zero, one rollout batch	
prompts	512
samples per prompt	16
maximum length	32K, later 64K tokens
generated tokens	up to $\approx$ 270M

Cost is about prompts $\times$ K $\times$ average length, plus the checker. Generating is slow autoregressive decoding, so most of an RL step is inference, and the slowest response holds up the step.

For an agent the response is a whole trajectory, and V checks the final state, for example whether all tests pass after the patch. One number at the end has to be shared across thousands of tokens.

DeepSeek-R1 (arXiv 2501.12948 v2) §2.1. Token count is an upper bound from the length limit.

GRPO scores each response against the others for the same prompt



Six samples for one prompt, three correct. Correct answers are pushed up and wrong ones down.

$$A_i = \frac{r_i - \mathrm{mean}(r_1, \ldots, r_G)}{\mathrm{std}(r_1, \ldots, r_G)}$$

GRPO uses the group of samples for one prompt as its own baseline. PPO needs a separate value model the size of the policy for this, so GRPO saves that memory.

If every sample gets the same reward, all advantages are zero and the prompt teaches nothing.

DeepSeek-R1 used two rule-based rewards, one for a correct answer and one for the format that makes the answer checkable.

Shao et al., DeepSeekMath (arXiv 2402.03300); DeepSeek-R1 (arXiv 2501.12948).

RL alone produced long chains of thought in DeepSeek-R1-Zero



Curve shapes sketched after R1 Fig. 1. Start and end values are from the paper.

The base model was trained with GRPO and the two rule-based rewards, with no SFT. Accuracy and response length rose together, and nobody wrote a long chain of thought for the model to copy.

R1-Zero's outputs were hard to read and mixed languages. The released R1 adds SFT on curated reasoning traces before RL, then rejection sampling, more SFT, and a final RL stage for general chat.

Longer responses also make every later RL step more expensive.

DeepSeek-AI, DeepSeek-R1 (arXiv 2501.12948; Nature 2025) Fig. 1.

A checker that can be fooled teaches the model to fool it



$$V(x, y) = \mathbf{1}[\text{format}] \cdot \mathbf{1}[\text{correct}] \cdot \mathbf{1}[\text{safe}]$$

A checker must be cheap enough to run on millions of samples, and it should rarely pass a wrong answer.

If wrong answers can pass, RL finds them. In OpenAI's coding RL runs, models learned to make the tests pass without fixing the code.

Hidden tests, strict answer parsing, and a stricter grader at evaluation time make the checker harder to fool.

Baker et al., Monitoring Reasoning Models for Misbehavior (arXiv 2503.11926).

RL environments package tasks, tools, and checkers



An environment holds the task, executes the model's tool calls, and returns a reward. Agentic RL needs environments that actually run tools, which static prompt sets cannot do.

One checker does not cover many skills, so labs train on suites of environments. Procedural generators such as Reasoning Gym create unlimited problems at a chosen difficulty, so the tasks stay near what the model can just barely solve.

NVIDIA NeMo Gym; Stojanovski et al., Reasoning Gym (arXiv 2505.24760); Zeng et al., RLVE (arXiv 2511.07317).

6. Evaluation

Turning model behavior into decisions

Evaluation decides which checkpoint ships and what to train on next



A model is checked on fixed benchmarks, by real users, and by people trying to break it. Each of these can block a release.

A model is evaluated on many separate capabilities

Knowledge
MMLU, MMLU-Pro, TriviaQA, Natural Questions, SimpleQA

Commonsense
ARC-Easy, ARC-Challenge, PIQA, SIQA, WinoGrande, HellaSwag, OpenBookQA, CommonsenseQA

Reading and reasoning
BoolQ, DROP, LAMBADA, BIG-Bench Hard

Math and science
GSM8K, MATH, AIME, GPQA, Humanity's Last Exam

Coding
HumanEval, MBPP, LiveCodeBench, SWE-bench Verified

Instructions and chat
IFEval, AlpacaEval, MT-Bench, Arena-Hard

Long context
RULER, LongBench v2, MRCR

Tool use and agents
BFCL, τ^2-bench, Terminal-Bench, OSWorld, BrowseComp

Multilingual
MGSM, MMMLU, INCLUDE, WMT24++

plus safety and refusal tests, truthfulness, human ratings of chat quality, and cost and latency

Model reports list dozens of these benchmarks. New checkpoints are run on many of them, because a change aimed at one area can move the others.

Improving one capability can make another worse

Change	What improved	What got worse
RLHF in InstructGPT	people preferred its answers to GPT-3's	scores on SQuAD, DROP, HellaSwag, and WMT translation dropped
RLHF in GPT-4	helpfulness and instruction following	calibration on MMLU, with expected error rising from 0.007 to 0.074
Reasoning RL, o1 to o3	math, coding, and science benchmarks	hallucinations on PersonQA, from 16% to 33% of answers

Getting one model to be good at everything is hard. InstructGPT reduced its losses by mixing pre-training data into the RL updates, and in general every change is checked against the whole evaluation suite before it is kept.

Ouyang et al., InstructGPT (arXiv 2203.02155) §4.2; OpenAI, GPT-4 Technical Report (arXiv 2303.08774) Fig. 8; OpenAI o3 and o4-mini System Card (Apr 2025).

Small benchmarks have wide error bars



$\mathrm{SE} = \sqrt{p(1-p)/n}$ with $p = 0.5$.

On a 30-problem benchmark, one problem is 3.3 points and the standard error of a single run is about 9 points. Reports average many samples per problem to bring this down.

Report results by slice as well as on average: with and without tools, short and long context, easy and hard, by language. Post-training changes help some slices and hurt others, and an average hides that.

Pass@1, majority vote, and pass@k measure different things



Illustration computed from one set of samples.

Pass@1 is what a user sees on one try.

Majority vote is what a product can get by sampling k times and picking the most common answer. It needs no checker.

Pass@k assumes a perfect checker picks the right sample, so it is an upper bound on what selection can do. High pass@k with low pass@1 means the model can find the answer but does not do so reliably.

Temperature, k, and the output length limit are part of the result and should be reported with it.

The same model gets different scores under different evaluation setups



Change	Effect on the score
Agent harness	With the same GPT-4 Turbo model, SWE-agent solved about 12% of SWE-bench issues, against about 1% for retrieval followed by one patch
Answer extraction	If the prompt does not ask for the answer in `\boxed{}`, correct answers can fail the extraction regex
Context management	Search agents that drop old tool results once context fills up score differently from ones that keep them
Output length limit	A tighter limit cuts off long reasoning before the answer

Yang et al., SWE-agent (arXiv 2405.15793) Table 1.

LLM judges prefer longer answers and answers shown first

Bias	What the judge does
Position	prefers the answer shown first, or second
Verbosity	prefers longer answers
Self-preference	prefers answers written by its own model family
Prompt sensitivity	changes its verdict when the judging prompt is reworded

Strong judges agreed with human experts about as often as experts agreed with each other on open-ended chat.

Judging each pair in both orders, calibrating against a set of human labels, and using several judges reduce these biases.

When a judge is also used as a reward in RL, its biases become things the policy can exploit.

Zheng et al., Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena (arXiv 2306.05685).

Benchmark questions in the training data inflate scores



Qwen2.5 shows signs of contamination on MATH-500 and AIME, and much early RL research used those models and benchmarks.

Benchmarks respond in three ways. Live benchmarks add fresh tasks over time, private sets are kept out of public data, and tasks built after a model's data cutoff (new contests, new repositories) cannot have been seen.

OLMo 3 released fully open, decontaminated training data so these effects can be checked.

Wu et al., Reasoning or Memorization (arXiv 2507.10532); LiveBench (livebench.ai); OLMo 3 (arXiv 2512.13961).

Failures found after release become new tests and training data



A gate states in advance what blocks a release, for example any safety regression above a threshold, schema validity below 99.9% on critical flows, or a latency budget exceeded. This makes the decision auditable.

The result should point to a fix. Protocol errors call for more SFT data, quality trade-offs for preference pairs, and task failures for better checkers and more RL.

Conclusion

- Everything the model sees is a token sequence. Post-training writes chat turns, tool calls, reasoning, and preferences into tokens through a chat template.
- The template, the loss mask, and the server's parsers have to agree. Tool definitions take context space, and how they are formatted changes what the model sees.
- A tool call is an action in a partially observed world, and tool results are untrusted input.
- SFT imitates demonstrations, and preference tuning learns from comparisons through a reward model or DPO. Pushing too hard on a learned reward lowers real quality.
- RLVR uses a checker as the reward. It needs a model that already gets some answers right and a checker that is hard to fool.
- A model is evaluated on many capabilities at once, and a gain in one can cost another. Scores also depend on the evaluation setup.